



URIT-810

Chemistry Analyzer

- ▶ High performance
- ▶ Easy operation & Maintenance

URIT-810

Chemistry Analyzer

| Specifications |

Analysis method: Kinetic, end point, non-linear, sample blank, reagent blank, etc

Light source: halogen lamp, 6V/10W

Wavelength range: 300~800nm

Absorbance range: -0.3~3.0Abs

Wavelength accuracy: ± 1 nm

Spectrum band: ± 6 nm

Flowcell: 10mm quartz cell, 32 μ L volume

Temperature control: Room temperature, 25°C, 30°C, 37°C, ($\pm 0.1^\circ\text{C}$ variable)

Sampling volume: 100 μ L~9999 μ L tunable

Cross contamination: $\leq 1.0\%$

Stability: ≤ 0.005 Abs/h

Memory: up to 234 items and 20000 test results

Display: Large LCD display

Printer: Built-in thermal printer

Interface: Serial port (RS232), Parallel port (For external printer)

Ambient: Room temperature: 10°C~32°C; Humidity: $\leq 85\%$

Power: AC 220x ($1 \pm 10\%$) V, 50Hz

Dimension: 392 x 375x 205mm (length * width * height)

| Features |

- High-quality filter & close optical system
- Convenient maintenance design
- Large memory capacity
- Advanced unexpected power-off protection

URIT MEDICAL ELECTRONIC (GROUP) CO., LTD.

Add: No.4 EAST ALLEY, JIUHUA ROAD, GUILIN, GUANGXI 541001, P.R.CHINA

Tel: +86 773 2288583/2288589 Fax: +86 773 2288560/2288559

E-mail: export@uritest.com service@uritest.com Http://www.urit.com

